

## TECHNICAL SHEET

# Econococos<sup>®</sup>

17, 20 & 23 mm



## DESCRIPTION

The walking surface consists of 100% spun coco fibres that are implanted on a PVC backing of 4 mm thickness.

## APPLICATION

Appropriate for low to traffic and for temporary solutions.

Traffic up to 100 passages daily

Locations Home, shop or office

## PRODUCTION

The mat is made to size. Dependent on the length of the walking direction, the Econococos is made in one piece, taking into account the width of the rolls 1 m, 1.5 m or 2m. For the price of the mat, the calculation is also based on the full roll width 1, 1.5 or 2 m in the walking direction. The required function and surroundings are relevant for the design and division of the mat.

## INSTALLATION

The height of the mat is 17, 20 or 23 mm and is installed in an even matwell of respectively 20, 20 or 25 mm. The corresponding built-in frame is made of anodised aluminium or brass.

## MATERIAL CHARACTERISTICS

### DRYING SURFACE

Material: cocos / 100 % spun coco fibres  
Colours (only in 17 mm height): grey (ref. 11), blue (ref. 12), red (ref. 16), black (ref. 17)  
Colours (20 & 23 mm height): natural

### BACKING

Material: PVC

## MAT CHARACTERISTICS

The total height of the mat is 17, 20 or 23 mm. The Econococos weighs respectively approximately 5, 6 or 7 kg/m<sup>2</sup>.

*Verimpex Matting reserves the right to make adjustments to the products without prior communication.*