



WHITE FROST

PERFORMANCE DATA

UV-range (280 – 380 nm)	>95%	
Visible range (380 – 780 nm) Visible Light Transmission (VLT)	69,1%	
Solar range (300 – 2.500 nm) Energetic Transmission	63%	
Energetic Reflection	18%	
Absorption	19%	

Manufacturer's warranty

10 year warranty against peeling and cracking
Metal free: no demetallization possible
Inside installation
Hard coat

Rolls 30,5 m x 1,52 m



Tested on single glazing (4mm) according to European standard NBN EN 410 and 12900. The technical results are subject to variations within industry standards. These test data only contain results that were obtained after the use of specific test procedures and standards. Extrapolation of the data of the sample or samples relating to the batch or lot from which data were obtained may not correlate and should be interpreted with caution. Umisol is not responsible for differences in quality, composition, appearance, performance, or other feature of a similar product produced by persons or under conditions over which Umisol has no control.
Copyright Umisol Group NV/SA. All Rights Reserved

MADE IN BELGIUM 



UMISOL IS PART OF GROUP MAM

Umisol Group • info@umisol.com • www.umisol.com

Belgium: Poldergotestraat 24 • B-9240 Zele • T: +32 (0)3 766 18 40

The Netherlands: Van Heuven Goedhartlaan 13 D • NL-1181 LE Amstelveen • T: +31 (0)76 541 49 90